



NEW IN BOX SKF QJ 211 MA/C3 Four point contact bearings, ID 55 mm, OD 100 mm

Bearing No. 211

211 Bearing 2D drawings and 3D CAD models

Size	100x55x21 mm
Bore Diameter	100 mm
Outer Diameter	55 mm
Width	21 mm
d	55 mm
D	100 mm
B	21 mm
d ₁	69.06 mm
D ₂	89.4 mm
r _{1,2} - min.	1.5 mm
d _a - min.	64 mm
D _a - max.	91 mm
r _a - max.	1.5 mm
Basic dynamic load rating - C	48.4 kN
Basic static load rating - C ₀	44 kN
Fatigue load limit - P _u	1.9 kN
Reference speed	12000 r/min
Limiting speed	7000 r/min
Calculation factor - k _r	0.04
Category	Single Row Ball Bearings
Inventory	6.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.68



EAN	7316576679759
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	Yes
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	55MM Bore; 100MM Outside Diameter; 21MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	211
Weight / LBS	1.49
Bore	2.165 Inch 55 Millimeter
Outside Diameter	3.937 Inch 100 Millimeter
Outer Race Width	0.827 Inch 21 Millimeter
bore diameter:	55 mm
static load capacity:	44 kN
outside diameter:	100 mm
precision rating:	ABEC 3 (ISO Class 6)



overall width:	21 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	21 mm
row type & fill slot:	Single Row Filling Slot
fillet radius:	1.5 mm
snap ring included:	Without Snap Ring
maximum rpm:	7000 RPM
internal clearance:	C0
series:	21
dynamic load capacity:	48.4 kN
thrust application warning:	This product can not be used in Thrust Applications
d_1	69.06 mm
D_2	89.4 mm
$r_{1,2}$ min.	1.5 mm
d_a min.	64 mm
D_a max.	91 mm
r_a max.	1.5 mm
Basic dynamic load rating C	48.4 kN
Basic static load rating C_0	44 kN
Fatigue load limit P_u	1.86 kN
Calculation factor k_r	0.04
Mass bearing	0.66 kg